



Focused on delivering energy **cleaner.**

Recompression
Pipeline Evacuation
Cross-Compression



CR offers a near zero methane emission alternative to pipeline evacuation.



Repair, maintain, and test your pipeline without venting or flaring natural gas.



Superior customer experience, safer operations, and a faster more environmentally friendly solution.

Peak Operational Efficiency

Purpose built design. More capacity in a smaller footprint, to put your pipeline back in service sooner.

No third-party trucking. Ease of mobility. Quick response times.



GENERAL

- Electric drive
- Compact footprint (32' L x 8.5' W) ea.
- Quiet operation (58 dBA @ 50 ft)

CODES AND STANDARDS

- API 500, Class 1, Division 2, Electrical Area Classification
- ASME Section VIII, Division I, Pressure Vessels
- ASME B31.3, Process Piping

SAFETY AND OVERPRESSURE PROTECTION

PLC

- Discharge overpressure shutdown

MECHANICAL

- Equipment - full flow Pressure Safety Valve (PSV) at each compressor stage
- Discharge PSV - adjusted for pipeline MAOP

PERFORMANCE

- 16,000,000 SCFD max flow rate ea.
- Contact us for more information

Patent pending

ESG

ENVIRONMENTAL SOCIAL GOVERNANCE



cleaner/greener



higher capacity



compact footprint

CLEAN
RECOMPRESSION

832-615-2576

sales@cleanrecompression.com

cleanrecompression.com



Scan QR code
to request a project
estimate

